USB-C 10-1 Mini Dock

Customizable USB-C Multiport Dock - Ethernet Port - 2 x DP - PD 85W - SD Card Reader

The USB-C 10-1 Mini Dock is a portable design between the office and home. This mini dock allows a mobile office to be set up in seconds with a single USB-C connection.



Features

- **Single USB-C connection for easy workspace setup** Connect your displays, network, and peripherals through a single USB-C connection to your laptop. Set up your workspace in seconds and move easily between office and home.
- **Dual 4K@60Hz DisplayPort outputs** Two DisplayPort 1.4 outputs support dual 4K@60Hz displays, giving you more room for multitasking. Requires a host that supports HBR3 and DSC 1.2.
- **USB-C PD 3.0 pass-through charging up to 85W** Supports USB-C PD 3.0 pass-through charging to deliver up to 85W of power to your laptop while using connected displays and peripherals. Requires a compatible USB-C PD power adapter.
- **Five USB-A 5Gbps ports for peripherals** Expand your laptop with five USB-A ports supporting data transfer rates up to 5Gbps. Connect keyboards, mice, external storage, and other USB peripherals to keep your essential devices within reach.
- **Gigabit Ethernet for wired networking** Add Gigabit Ethernet connectivity to your laptop for wired network access at speeds up to 1Gbps. Stay connected for video meetings, file transfers, and everyday office tasks.
- **Built-in SD 4.0 card reader** Access photos, videos, and documents directly from compatible SD cards with the built-in SD 4.0 card reader. Simplify file transfers without connecting a separate card reader.

Specifications

Model	VSD5480
Host / Upstream	
Upstream Port (Host)	USB-C (PD pass through up to 85W)
Host Interface	USB-C
Display	
Maximum Display	2 × 4K@60Hz
Legacy Video Port	2 × DisplayPort
Max Resolution	2x 4K60 (PC GPU supports HBR3+DSC1.2)
Video Output	DisplayPort

USB	
USB Downstream	5 × USB-A 5Gbps, 1 × USB-C (Power in only)
Network	
LAN	1 × RJ45 (1GbE)
Power	
PD	85W
Power Mode	Dual-Power
Audio & Other I/O	
Card Reader	SD
Physical	
Tethered Cable	300mm
Dimension (L x W x H)	100 x 100 x 29 mm
Operating Temperature	Operating: 0~40°C; Storage: -20~70°C
Housing	ABS (Plastic)
General	
Features	Ethernet, Card Reader, PD Charging