# USB-C DP1.4 MST Triple Video Docking Station

## Customizable portable docking station – Triple monitors – PD96W charging

The USB-C DP1.4 MST Triple Video Docking Station showcases outstanding performance through its robust screen expansion and seamless connectivity, enhancing productivity both in the office and at home. It has the capability to extend content across three monitors at a stunning 4K resolution using legacy DP and HDMI ports, significantly improving efficiency. Additionally, it incorporates PD charging technology, offering fast charging of up to 96W for laptops via the integrated USB-C interface. With four USB-A ports and USB-C ports on the Video Docking Station



## Features

- **Supports up to triple 4K30 displays with DP1.4 DSC technology.**
- **Features two DisplayPort 1.4 outputs and one HDMI 2.1 output.**
- **Delivers up to 96W USB-C PD charging for laptops.**
- **Provides two USB-C 10Gbps, two USB-A 10Gbps, and two USB-A 2.0 ports.**
- **Built-in Gigabit Ethernet and headset jack for convenient connectivity.**
- **Compatible with Windows and macOS, with limited MST support on Mac.**

## Specifications

| | |
|---|---|
| **Model** | DUD2170 |
| **Host / Upstream** | |
| **Upstream Port (Host)** | 1 × USB-C 10Gbps |
| **Host Interface** | USB-C |
| **Display** | |
| **Maximum Display** | 1 × 4K@120Hz, 2 × 4K@60Hz, 3 × 4K@30Hz |
| **Legacy Video Port** | 2 × DisplayPort, 1 × HDMI |
| **Max Resolution** | DP1.2 HBR2: 1× 4K30, 2× FHD60, 3× FHD30, DP1.4 HBR3: 1× 4K60, 2× QHD60, 3× FHD60, DP1.4 HBR3 DSC: 1× 4K120, 2× 4K60, 3× 4K30 |
| **Video Output** | DisplayPort, HDMI |
| **Display Technology** | MST |
| **USB** | |
| **USB Downstream** | 2 × USB-C 10Gbps, 2 × USB-A 10Gbps, 2 × USB-A USB 2.0 |
| **Network** | |

| | |
|---|---|
| **LAN** | 1 × RJ45 (1GbE) |
| **Power** | |
| **PD** | 96W |
| **Power Supply** | DC 135W |
| **Power Mode** | Self-Power |
| **Audio & Other I/O** | |
| **Audio** | 1× 3.5mm TRS (HS/MIC) |
| **Physical** | |
| **Dimension (L x W x H)** | 190 x 85 x 27 mm |
| **Operating Temperature** | Operating: 0~40°C; Storage: -20~70°C |
| **General** | |
| **Features** | Audio, Ethernet, PD Charging |